

HOSE END NOZZLES & ADAPTERS

Hose End Fill Nozzles & Adapters

Used in conjunction with ball, globe, angle, toggle or quick acting valves to adapt hoses to various container filling requirements. The adapters listed allow hose end valves designed for specific container valves to be adapted to various other valve styles. This, in turn, will also allow for multiple valve configurations to be filled with single hose dispensing systems.



NEE #	Inlet Size	Outlet Connection	Application	Notes	
M640-4	1 1/4" Female ACME	1/2" MNPT	Vapour Return Coupling	-	
ME390	1/4" M NPT	M POL	POL Cylinder Fill Nozzle, 6" OAL	Replacement O-ring (568-110-01)	
ME390S			ME390 with steel nipple	Replacement Stainless Steel Stem (ME390SWR-1)	
ME388			POL Cylinder Fill Nozzle, 2 11/16" OAL	-	
ME515			QCC Cylinder Fill Nozzle, 7" OAL	EZ Grip Handle	
ME516		F. 1-5/16" Type 1 ACME	QCC Cylinder Fill Nozzle, 6" OAL	Standard Grip with Hand wheel	
ME516S			QCC Cylinder Fill Nozzle (Stainless Steel Nipple), 6" OAL		
ME392			QCC Cylinder Fill Adapter, 2 1/2" OAL		-
ME393		F. POL	M POL	QCC Cylinder Fill to POL Adapter, 2 1/2" OAL	Round Brass Handwheel
ME393HD		M. 1-5/16" Type 1 ACME	F 1-1/4" ACME	QCC fill to Forklift	Forged Brass Handwheel
ME394					F 1-3/4" ACME
ME569	1/4" F NPT				
ME393-1	1 1/4" F Lift Truck valve				
ME790	1/4" M NPT				1 1/4" F ACME
ME795	1/4" M NPT	1 1/4" F ACME	Forklift Quick Filler	Replacement Tip Seal (ME795-3-02), Low Emission	
ME568		F. POL	1 3/4" F ACME	Short Brass POL to ACME Adapter	With Swivel ACME

PLANT, TRUCK & TANK EQUIPMENT

Filler Hose Check Valve Adapters



These adapters are intended to be attached to the LP gas delivery truck hose outlet. All have minimal flow restriction and a single back check valve that will allow the driver to leave it on the container valve in the event of a filler valve failure, preventing the loss of product and allowing the driver to wait until the container is emptied before attempting valve repair. The **ME571H High Capacity Safety Fill Adapter** features the industry's highest flow rate of 86 GPM LPG @ 30 PSI pressure differential.

NEE #	Inlet	Outlet	Notes	
ME570	1 3/4" M. ACME	1 3/4" F. ACME Non-Swivel	-	
ME571		1 3/4" F. ACME Swivel		
ME571H		1 3/4" F. ACME High Capacity Hose End Check Adapter	High Capacity Safety Fill Adapter	
ME572		1 3/4" F. ACME Swivel	1 3/4" F. ACME Swivel	Single piece brass body
ME574				With Bleeder Vent Valve
ME578				Full flow ball valve shut-off
M570		1 3/4" F. ACME Non-Swivel	Outer washer T13098 / Inner T13103	

Replacement Part

NEE #	Description
ME578-02	Replacement Key for ME578